SmartPro XL Expandable Tower UPS System

Intelligent, line-interactive battery backup and network power management



Model #: SMART1050XL

- 1050VA line interactive tower UPS system
- Enhanced communications ports (1 USB / 1 DB9), free PowerAlert software and cabling
- Corrects brownouts and overvoltages from 75 to 147V
- 1 load bank, 6 outlets
- Expandable runtime
- \$250,000 Ultimate Lifetime Insurance (USA & Canada only)

DESCRIPTION

Tripp Lite's SMART1050XL intelligent, line interactive UPS system protects servers, networking accessories and telecommunications equipment from blackouts, voltage fluctuations and transient surges. Large internal batteries offer 19 minutes half load runtime and 8 minutes at full load during power failures. Runtime is expandable with the addition of BP36V27 external battery packs. 1050VA / 800 watt power handling capability supports a variety of networking, telecom and various other applications. Includes a total of 6 outlets, 1 of which can be individually powered on and off via software interface to selectively reboot remote equipment or to automatically shed less significant loads to extend battery runtime for more critical equipment. Supports remote monitoring of UPS and site power conditions via built-in USB and DB9 monitoring ports. Includes PowerAlert UPS monitoring and unattended shutdown software with complete cabling. Supports SNMP with optional SNMPWEBSOLO external adapter. Notification of system status via 5 LEDs and multi-function audible alarms. Wall mountable with UPSWM wallmount bracket. Network-grade AC surge suppression protects equipment from damage and performance problems resulting from transient surges. Attractive, small-footprint tower housing uses less than 66 square inches of floor or desktop space. Two year warranty with \$250,000 connected equipment insurance.

KEY BUYING POINTS

- SMART1050XL line interactive UPS system offers voltage regulation and battery support, plus network-grade AC surge suppression to
 prevent equipment damage, data loss and downtime due to power problems
- 1050VA / 800 watt power handling capability supports a variety of networking, telecom and various other application types
- Internal batteries offer 19 minutes half load runtime and 8 minutes at full load
- Runtime is expandable with the addition of BP36V27 external battery packs
- Automatic Voltage Regulation (AVR) circuits with two boost and one voltage reduction level maintains usable 120V nominal output over an input voltage range of 75-147V
- Includes a total of 6 NEMA5-15R outlets, 1 of which can be individually powered on and off via software interface to selectively reboot remote equipment or automatically shed less significant loads to extend battery runtime for more critical equipment
- Includes 1 USB and 1 DB9 monitoring port for remote monitoring of UPS and site power status
- Monitoring ports support messaging of UPS and line power status, including on-battery, low-battery, power-restored, AC line voltage, DC battery voltage and battery capacity
- UPS interface supports timed inverter shutoff after unattended shutdown, activate self-test and 10 second reboot of connected equipment
- PowerAlert UPS monitoring and unattended shutdown software with complete USB and DB9 cabling included
- Supports SNMP in large network applications with optional SNMPWEBSOLO external adapter
- Supports Tripp Lite's WatchDog software application to restore unresponsive programs by automatically restarting them and rebooting completely locked computers by automatically switching UPS power off and back on again
- 5 front panel LEDs and multi-function audible alarms offer status of line power, battery power, battery low/replace, voltage regulation and load level
- Wall mountable with UPSWM wallmount bracket
- Attractive small footprint beige tower housing uses less than 66 square inches
- Built-in rear-exit cooling fan runs as needed to maintain optimal internal temperatures, especially during extended run battery operation
- Hot-swappable / user replaceable batteries allow on-site battery replacement
- UPS battery set ships fully assembled and ready for installation, no time consuming connection of internal batteries by user is necessary

- Cold start capability enables UPS turn-on in battery mode during blackout conditions
- UL (USA), cUL (Canada), NOM (Mexico), FCC Class A (Business) Listed
- \$250,000 Ultimate Lifetime Insurance. No warranty cards required for coverage!
- 2 year manufacturers product warranty

TYPICAL APPLICATIONS

•	 Ideal for the protection of fileservers, netw 	ork accessories ar	nd telecommunic	cations equipmer	nt. Common app	plications include	e any mix
	of servers, workstations, hubs, routers,	concentrators, IP	telephony and	traditional PBX	switching sys	tems. Ideal for	sensitive
	electronic applications in areas where brownouts and overvoltages are common.						