

SmartOnline Expandable Rack / Tower UPS System

Online, double-conversion protection for mission critical applications



Model #: SU3000RTXL3UHV

- ▶ 3000VA online 3U rack / tower UPS
- ▶ Enhanced serial communications port and SNMP/Web card slot
- ▶ Maintains output within 2% of selectable 200/208/220/230/240V nominal during overvoltages to 275 and brownouts as low as 130V
- ▶ 9 outlets (6-15/20, L6-20)
- ▶ Expandable runtime with optional BP72V122U external battery pack
- ▶ \$250,000 Ultimate Lifetime Insurance (USA & Canada only)

DESCRIPTION

Tripp Lite's high voltage SmartOnLine SU3000RTXL3UHV on-line, double conversion UPS protects critical server, networking or telecommunications equipment from blackouts, voltage fluctuations and surges. Multi-use form factor occupies only 3 rack spaces (3U) in standard 19 inch rackmount configuration and includes tower stands to support upright placement. Large capacity 3kVA / 2400 watt UPS continuously converts incoming AC to DC, then back to perfect sine wave AC output at selectable 200/208/220/230/240V AC (+/-2%) output. Removes harmonic distortion, fast electrical impulses, frequency fluctuations and other hard-to-solve power problems not addressed by other UPS types. True sine wave output and zero transfer time offers guaranteed compatibility with all high-voltage equipment types. Includes 8 outlets arranged in two individually switchable load banks and 1 L6-20 outlet. These outlet banks can be independently controlled via software interface to selectively reboot remote equipment, or shed less critical loads to extend battery runtime for more critical equipment. Battery support can be extended indefinitely through the addition of external 2U rackmount battery packs (part# BP72V122U). Includes slot for internal SNMP/web card, plus DB9 enhanced serial monitoring port for unattended shutdown, remote control and monitoring of UPS system and power data. Compatible with Tripp Lite's WatchDog™ Service Monitoring/Reboot Software.

KEY BUYING POINTS

- True on-line, double conversion UPS provides pure, sine wave AC output at all times
- Maintains continuous operation through blackouts, voltage fluctuations and surges with zero transfer time
- Removes harmonic distortion, electrical impulses, frequency variations and other hard to solve power problems
- Accepts input voltages between 160 and 275 (130 to 275 at loads under 70%), regulating output to selectable 200/208/220/230/240V +/-2%
- 3000VA / 2400 watt power capacity with 9 total outlets (8 NEMA6-15/20R & 1 NEMAL6-20R)
- Standard internal battery set provides 17 minutes runtime at half load
- Expandable runtime with multiple external battery packs (part# BP72V122U)
- Innovative design makes unit adaptable for rackmount, tower, or stacking applications
- Uses only 3 rack spaces (3U) in standard 19 inch rack
- DB9 serial port for network interface; SNMP compatible
- Slot for optional SNMP/web card (part# SNMPWEBCARD)
- PowerAlert unattended shutdown software and 6 ft. network cable included
- Compatible with Tripp Lite's Watchdog Service Monitoring/Reboot Software
- \$250,000 Ultimate Lifetime connected equipment insurance
- 2 year manufacturer's product warranty
- Diagnostic LEDs
- Battery replacement door
- Mounting hardware included for 4 post rack enclosures, 2 post telecom rack compatible with separate purchase 2POSTRMKIT accessory

TYPICAL APPLICATIONS

- Ideal for protection of critical high-voltage equipment in server rooms, internetworking closets and telecommunications systems in

rackmount or tower applications. Common applications include corporate or departmental servers, workstations, hubs, routers, bridges, CAD/CAM workstations, concentrators, IP telephony and traditional PBX switching systems.
