

SmartOnline Expandable Rack / Tower UPS System

On-line, double-conversion protection for mission-critical applications



Model #: SU6000RT3UXR

- ▶ 6000VA on-line 12U rack / tower UPS (3U power module + 3U step-down transformer + two 3U battery packs)
- ▶ Enhanced serial communications ports, SNMP/web card slot and EPO jack
- ▶ Maintains 200, 208, 220, 230 or 240V and simultaneous 100, 120V output +/-2% during brownouts to 156 and overvoltages to 276V
- ▶ Hardwire input / output connections
- ▶ Expandable runtime with optional BP240V10RT3U battery packs (includes two)
- ▶ \$250,000 Ultimate Lifetime Insurance (USA & Canada only)

DESCRIPTION

Tripp Lite's SU6000RT3UXR on-line, double conversion UPS protects server, networking or telecommunications equipment from blackouts, voltage fluctuations and surges in a tower/rackmount housing. In rack configuration, power module, step-down transformer and two battery packs occupy 3 rack spaces each (12U total). Upright tower placement for up to 9U supported with included tower stands. Large capacity 6000 VA / 4200 watt power module converts raw input AC to DC, then back to perfect sine wave AC output within 2% of user-selectable 200/208/220/230/240V and 100/120V AC output voltages. Frequency regulation locks output power to 50/60Hz (+/-0.2 Hz), removing harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types. Perfectly regulated, continuous sine wave output with zero transfer time offers compatibility with all equipment types. Hardwire input and output connections support a variety of permanent or PDU style power connections. Battery support can be extended indefinitely through the addition of external 3U rackmount battery packs (part# BP240V10RT3U). Includes slot for internal SNMP/web card, plus 2 DB9 enhanced serial monitoring ports (1-RS232 / 1-contact closure) for unattended shutdown, remote control and monitoring of UPS system and power data.

KEY BUYING POINTS

- True on-line, double conversion UPS provides pure, sine wave AC output at all times
- Maintains continuous operation through blackouts, voltage fluctuations and surges with zero transfer time
- Removes harmonic distortion, electrical impulses, frequency variations and other hard-to-solve power problems
- 6000VA/4200 watt power capacity with hardwire input / output connections
- Accepts input voltages between 156 and 276, regulating output within 2% of selectable 200/208/220/230/240V and 100/120V AC output
- Included 3U battery pack provides 79 minutes runtime at half load (3000VA) and 37 minutes at full load (6000VA)
- Expandable runtime with multiple external battery packs (part# BP240V10RT3U) (two included with SU6000RT3UXR)
- Innovative design makes unit adaptable for rackmount or upright tower placement (included stands support up to 9U in upright tower configuration - purchase additional 2-9USTAND accessory for full system tower support)
- Power module, transformer module and battery pack require only 3 rack spaces each (12U total rack space usage)
- DB9 serial port for network interface; SNMP compatible
- Slot for optional SNMP/web card SNMP/Web card for accessory slot (SNMPWEBCARD)
- Includes PowerAlert UPS monitoring and unattended shutdown software and 6 ft. network cable included
- \$250,000 Ultimate Lifetime connected equipment Insurance (USA & Canada Only)
- 2 year manufacturer's product warranty
- Diagnostic LEDs
- Mounting hardware included with each 3U module for 4 post rackmount installation, 2 post telecom rack compatible with separate purchase 2POSTRMKIT accessory (4 required)
- Included tower stands support up to 9U in upright vertical form factor (order additional 2-9USTAND accessory for full 12U tower support)

TYPICAL APPLICATIONS

- Ideal for protection of critical 200/208/220/230/240V and 120V equipment in server rooms, internetworking closets and telecommunications systems in rackmount or tower applications. Common applications include corporate or departmental servers, workstations, hubs, routers, bridges, CAD/CAM workstations, concentrators, IP telephony and traditional PBX switching systems.
-